

SK5002

Double Channel
Semi-auto
Coagulation Analyzer



Features

- Low reagent consumption less than 20u L, open reagent.
- Special testing cup location system, adding sample bracket
- Advanced optical light matching system ensure precision result.
- Optional PT Derived method for testing fibrinogen, decrease the dosage of reagent
- Top quality thermostat, precision $37^{\circ}\text{C} \pm 0.3^{\circ}\text{C}$
- Dispense precision: $\text{CV} < 2\%$
- Memory for 10,000 testing result
- Internal thermal-sensitive printer
- Electronically-linked pipette optional.
- Perform all routine tests such as PT, APTT, TT Fibrinogen and clotting factors
- RS232 interface, PC connecting



Specifications

- *Test channel number: 2 channel; 2 different parameters analysis in the same time*
- *Sample incubation block: 16 positions*
- *Reagent incubation block: 4 positions*
- *Software timer: 2*
- *Test wavelength: 470nm*
- *Memory: 10000 test result*
- *Temp control precision: $37 \pm 0.3^{\circ}\text{C}$*
- *Sample consume: 20uL-40uL*
- *Reagent consume: 20uL-40uL*
- *Coincidence indicator: $\leq 3\%$*
- *Notation of Result: S, %, PTR, INR, g/L*
- *Operation language: English*
- *Screen: 128*240 LCD*
- *Power supply: 220 VAC $\pm 15\%$ 50-60 HZ*
- *Dimensions: 395mm(L)*320mm(W)*135mm(H)*
- *Work environment: temperature $15^{\circ}\text{C}-30^{\circ}\text{C}$ wet $\leq 90\%$*
- *Weight: 6Kg*

SK5002

