

# SK5004

Four Channel  
Semi-auto  
Coagulation Analyzer



## Features

- Low reagent consumption less than 20u L, open reagent.
- Special testing cup location system, adding sample bracket
- Advanced optical light matching system ensure precision result.
- Optional PT Derived method for testing fibrinogen, decrease the dosage of reagent
- Top quality thermostat, precision 37°C ±0.3°C
- Dispense precision: CV<2 %
- Memory for 10.000 testing result
- Internal thermal-sensitive printer
- Electronically-linked pipette optional.
- Perform all routine tests such as PT. APTT. TT Fibrinogen and clotting factors
- RS232 interface, PC connecting



## Specifications

- *Test channel number: 4 channel; 4 different parameters analysis in the same time*
- *Sample incubation block: 24 positions*
- *Reagent incubation block: 6 positions*
- *Software timer: 4*
- *Test wavelength: 470nm*
- *Memory: 10000 test result*
- *Temp control precision:  $37 \pm 0.3^{\circ}\text{C}$*
- *Sample consume: 20uL-40uL*
- *Reagent consume: 20uL-40uL*
- *Coincidence indicator:  $\leq 3\%$*
- *Notation of Result: S, %, PTR, INR, g/L*
- *Operation language: English*
- *Screen: 128\*240 LCD*
- *Power supply: 220VAC  $\pm$  15% 50-60 Hz*
- *Dimensions: 395mm(L)\*320mm(W)\*135mm(H)*
- *Work environment: temperature  $15^{\circ}\text{C}-30^{\circ}\text{C}$*
- *Wet  $\leq 90\%$  Weight: 7Kg*

# SK5004

